# **SAFETY DATA SHEET**



## 1. Product and Company Identification

**Product identifier** 

Other means of identification

Recommended use

**Recommended restrictions** 

20SOLUDGRAIS04 SOLUTION DEGREASER

Not available

All Purpose Cleaner None

known.

Emergency Phone (CANUTEC Emergency only): (613) 996-6666

### 2. Hazards Identification

GHS classification in accordance with: (CAN) WHMIS 2015

Physical hazardsCorrosive to metalsCategory 1Health hazardsEye damage/irritationCategory 1Skin corrosion/irritationCategory 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Signal word

**Danger** 

Hazard statement May be corrosive to metals

Causes severe skin burns and eye damage.

**Precautionary statement** 

Prevention

protective gloves/protective clothing/eye protection/face protection.

**Response** IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

None

**IF INHALED**: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present

and easy to do – continue rinsing. Immediately call a POISON CENTER/doctor.

Specific treatment (see this label). Wash contaminated clothing before reuse. Absorb spillage to

prevent material damage.

Storage Keep only in original container. Store locked up. Store in a corrosive resistant container or a

container with resistant inner liner.

Dispose of contents/container in accordance with local/regional/national/international regulations.

DisposalDisposeHazard(s) not otherwiseNone kn

nazaru(s) not otnerwise

classified (HNOC)

Supplemental information

None known.

## 3. Composition/Information on Ingredients

Mixture Chemical name	Common name and synonyms	CAS number	%
Sodium Silicate		6834-92-0	1 – 5
2-Butoxyethanol		111-76-2	1 - 5

### 4. First Aid Measures

Inhalation

Skin contact

If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor/.

Eye contact

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Specific treatment (see product label). Immediately call a poison center/doctor/.

**Ingestion Most** important

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.

symptoms/effects, acute and delayed immediate of

If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center/doctor/. Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

Indication medical attention and special treatment needed General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Wear rubber gloves and chemical splash goggles. Keep out of reach of children.

## 5. Fire Fighting Measures

Treat for surrounding material.

Suitable extinguishing media Unsuitable extinguishing media

Use appropriate extinguisher, as surrounding material.

Firefighters should wear a self-contained breathing apparatus. Specific hazards arising from the

chemical

Firefighters should wear full protective clothing including self contained breathing apparatus.

Special protective equipment and

precautions

Move containers from fire area if you can do so without risk.

firefighters Fire-fighting equipment/instructions Specific methods

6. Accidental Release Measures

Hazardous combustion

Use standard firefighting procedures and consider the hazards of other involved materials. May include and are not limited to: Carbon oxide

products

Not available.

**Explosion data** 

Sensitivity to mechanical

impact

Not available.

Sensitivity to static

discharge

#### precautions. Personal protective equipment and emergency procedures

Keep unnecessary personnel away. Keep out of low areas. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. Should not be released into the environment.

## Methods and materials for containment and cleaning up

Large Spills: Stop leak if you can do so without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb spillage to prevent material damage. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Prevent entry into waterways, sewers, basements or confined areas.

Avoid discharge into drains, water courses or onto the ground. Do not discharge into lakes, streams, ponds or public waters.

## **Environmental precautions**

## 7. Handling and Storage

#### Precautions for safe handling

Use only with adequate ventilation. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material. Avoid breathing vapors or mists of this product. DO NOT get in eyes, on skin or clothing.

### Conditions for safe storage, including any incompatibilities

Store locked up. Store in corrosive resistant container with a resistant inner liner. Keep only in the original container. Store in a cool, dry place out of direct sunlight. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure Controls/Personal Protection

### Occupational exposure limits

Components

Value

Sodium silicate 2-Butoxyethanol Exposition limit: 2mg/m3 (15 min TWA)

TWA: Concentration maximale: 20 ppm ACGIH

**Biological** limit Appropriate engineering controls

values No biological exposure limits noted for the ingredient(s).

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation,

or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Individual protection measures, such as personal protective equipment

Eye/face protection

Chemical splash goggles.

Skin protection Hand

protection

Chemical resistant gloves. Confirm with a reputable supplier first.

Other

hygiene considerations

Wear appropriate chemical resistant clothing. As required by employer code. Where exposure

guideline levels may be exceeded, use an approved NIOSH respirator.

Respiratory protection

Thermal hazards General

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Wash hands before breaks and immediately after handling

the product.

Not applicable.

## 9. Physical and Chemical Properties

**Appearance** Clear Physical state Liquid. **Form** Liquid Color Orange Odor Cherry **Odor threshold** Not available.

pН > 13.0 Melting point/freezing point 0°C Initial boiling point and boiling

range

100 °C

Pour point Partition coefficient (nNot available. Not available

octanol/water)

Flash point

> 94°C

**Evaporation rate** Flammability (solid, gas) Not available Not applicable. Upper/lower flammability or explosive limits

**Flammability** Not available

limit - lower (%)

**Flammability** Not available

limit - upper (%)

Explosive limit - Not available.

lower (%)

Explosive limit -Not available.

upper (%)

Not available Vapor pressure Vapor density Not available

Relative density 1.03 Solubility(ies) Complete **Auto-ignition** Not available

temperature

Decomposition

Not available.

temperature

**Viscosity** Not available.

## 10. Stability and Reactivity

Strong acids product This may react with Reactivity oxidizing Possibility of agents. hazardous reactions Hazardous polymerization Chemical does not occur. stability **Conditions to** Stable under recommended storage avoid conditions. Incompatible Reacts with strong acids. This materials

product may react with oxidizing Hazardous agents.

decomposition

products Oxidizing agents. Acids.

May include and are not limited to:

Carbon oxide

## 11. Toxicological Information

Routes of exposure Eye, Skin contact, Inhalation, Ingestion.

Information on likely routes of exposure

Ingestion Causes digestive tract burns.

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes severe skin burns. Eye contact Causes serious eye damage.

Symptoms related to the Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may physical, chemical and include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including toxicological characteristics blindness could result.

### Information on toxicological effects

#### **Acute toxicity**

Addic toxicity		
Components Sodium silicate	Species	Test Results
Acute		
DermalDL50	Rat	> 5000 mg/kg
Inhalation CL50	Rat	>2.06 g/m <sup>3</sup> (4Heures)
Oral	Rat	3400 mg/kg
2-Butoxyethanol <b>Acute</b>		
Oral LD50	Rat	1300 mg/kg
Dermal LD50	Rat	> 2000 mg/kg

Skin corrosion/irritation Causes severe skin burns and eye damage.

**Exposure minutes** Not available. Erythema value Not available. Oedema value Not available.

Serious eye damage/eye

irritation

Causes serious eye damage.

Corneal opacity value Not available. Iris lesion value Not available.

Conjunctival reddening

value

Not available.

Not available.

Conjunctival oedema value Not available.

## Respiratory or skin sensitization

Respiratory Not available.

sensitization This product is not expected to cause skin sensitization.

Non-hazardous by WHMIS/OSHA criteria. Skin sensitization Non-hazardous by WHMIS/OSHA criteria.

None Germ cell

Recover days

Non-hazardous by WHMIS/OSHA criteria. mutagenicity Non-hazardous by WHMIS/OSHA criteria. Mutagenicity

Not classified. Carcinogenicity

Reproductive

toxicity

Not classified.

**Teratogenicity** Specific

Not available.

toxicity organ

target Prolonged inhalation may be harmful.

Not available. single exposure Not available. **Specific** target

organ toxicity repeated exposure Aspiration hazard **Chronic effects** 

**Further information** 

Name of **Toxicologically Synergistic Products** 

### 12. Ecological Information

### **Ecotoxicity**

Components	Species	Test
0 11 111 1	F: 1 (D 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Results
Sodium silicate	Fish (Brachydanio rerio) LC50 (96 hours)	1108 mg/l
Aquatic invertebrates (Daphnia magna) EC50(48 hour)		1700 mg/l
2-Butoxyethanol	LC50 Fish (Rainbow Trout) ( 96 hours)	1474 mg/l
	EC50 Daphnia magna ( 48 hours )	1550 mg/l
	EC50 Algae (72 hours)	1840 mg/l

Persistence and degradability Biodegradable at 100 %. **Bioaccumulative potential** No data available Mobility in soil No data available

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone

creation potential, endocrine disruption, global warming potential) are expected from

this component.

## 13. Disposal Consideration

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material **Disposal instructions** 

and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container

is emptied.

## 14. Transport Information

Canada: TDG Proof of Classification: In accordance with Part 2.2.1 (SOR/2014-152) of the General

Transportation of Dangerous Goods Regulations, we certify that the classification of this product is correct as of the SDS date of issue. If applicable, the technical name and the classification of the product will appear below. U.S.

**Department of Transportation (DOT) Basic shipping requirements:** 

> **UN** number UN1760

Proper shipping name Corrosive liquids, n.o.s. (Sodium silicate)

**Hazard class Packing group** Ш



### Transportation of Dangerous Goods (TDG - Canada)

**Basic shipping requirements:** 

**UN** number UN1760

Proper shipping name CORROSIVE LIQUID, N.O.S. (Sodium silicate)

**Hazard class** 8 Ш Packing group

### 15. Regulatory Information

Canadian federal regulations This product has been classified in accordance with the

criteria of the Controlled Products Regulations and the SDS the information required by the Controlled Products

WHMIS status Controlled


WHMIS classification Class E - Corrosive Material

WHMIS labeling

hazard contains all Regulations.



### 16. Other Information




Disclaimer

Issue date Effective date

**Further information** 

Other information





The data contained in this material safety data sheet was obtained from sources that were technically accurate, reliable, and state of the art when this document was prepared. If data was unavailable to complete certain sections, the absence of that data is identified in this document. Because the supplier cannot know the exact circumstances during actual use of this product, other hazards, exposure scenarios, disposal considerations, and regulations may apply and it is the responsibility of the user to read and understand the product label and this document before use. Do not use the product for purposes other than those stated in Section 1.

October 24, 2018

October 24, 2018

Version 2.0

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.

This Safety Data Sheet was prepared to comply with the current OSHA Hazard Communication Standard (HCS) adoption of the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).