

DATA SHEET

GREASE TRAP SOLUTION



DESCRIPTION :

Grease trap solution is an organic product. This product breaks down grease and other organic waste in grease traps, pipes, and drains. Grease trap solution controls and effectively eliminates odors caused by the accumulation of decomposing organic matter.

DIRECTIONS :

For major odor problems, use 350 to 500 mL of Grease trap solution in grease traps, pipes and drains attached to it. For minor smells, prepare a solution of 250 mL of fresh water and 250 mL of Grease trap solution and pour the solution into the pipes. As a preventive treatment, repeat the procedure once a week. Shake before use. Protect from freezing. Avoid contamination with food. Grease trap solution is not effective in the presence of chemical stabilizers such as formaldehyde or chlorine bleach. Disposal of empty containers: Empty containers should be recycled or disposed of through an approved facility for waste management.

CAUTION :

MAY IRRITATE EYES MAY IRRITATE SKIN. Do not get in eyes. Do not get on skin or clothing. Keep out of reach of children.

FORMAT	CODE
4 L	33SOLUTRAP04
10 L	33SOLUTRAP10


SPECIFICATIONS

Physical state and appearance	Transparent liquid
Color	Green
Odour	Lemon
P.H.	4,7 - 5,3
Melting / freezing	~ 0°C
Entreposage	Store in a cool, dry, well ventilated (0°C - 32°C) away from sunlight.
Lifetime	1 1/2 year

FIRST AID TREATMENT :

Contains: sodium dodecylbenzenesulfonate.

If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water.

350-500 ML PAR UTILISATION 
350-500 ML BY USE

ServitechXpert enr.
C.P 2, Saint-Constant, (Quebec)
J5A 2G1

Telephone: **514.475.8974**
Toll Free: **1.855.200.8974**
Fax: **450.638.8974**

www.servitechxpert.com

